






Standard Colors



Shasta White



Parchment



Almond



Sierra Tan




Buckskin



Medium Bronze



Aged Bronze



Copper Brown




Dark Bronze




Terra-Cotta



Deep Red



Colonial Red



Burgundy



Bristol Blue



Royal Blue



Patina Green



Hemlock Green



Teal Green



Forest Green



Evergreen



Hartford Green




Cityscape



Zinc Grey




Charcoal Grey



Matte Black

Premium Colors


Berridge premium colors require a nominal surcharge.



Natural White



Award Blue



Champagne




Copper-Cote™




Antique
Copper-Cote

Natural Metal Finish


Berridge Acrylic-Coated Galvalume® is a coated sheet product that combines the corrosion resistance of Galvalume® steel sheet with a clear, organic resin applied to the top side and bottom side of Galvalume® substrate.



Acrylic-Coated
Galvalume®



Zinc-Cote™



Lead-Cote™



Prewathered
Galvalume®

Metallic Colors

Berridge metallic colors are premium finishes which require a nominal surcharge.

BERRIDGE STOCK AVAILABILITY AND COLOR DETAILS

S - Stock Color N - Non-Stocking Color N/A - Not Available

Standard Colors	24 Gauge		22 Gauge*		0.032 Aluminum*		0.040 Aluminum*		SR	EM	SRI
	48"	42"	48"	42"	48"	42"	48"	42"			
Aged Bronze	S	S	S	N	S	N	S	N/A	0.30	0.86	30
Almond	S	S	S	N	S	N	S	N/A	0.65	0.83	77
Bristol Blue	S	S	N	N	N	N	N	N/A	0.33	0.85	33
Buckskin	S	S	S	N	N	N	N	N/A	0.32	0.83	32
Burgundy	S	S	N	N	N	N	N	N/A	0.29	0.85	29
Charcoal Grey	S	S	S	N	N	N	N	N/A	0.31	0.84	30
Cityscape	S	S	N	N	N	N	N	N/A	0.48	0.85	54
Colonial Red	S	S	N	N	N	N	N	N/A	0.33	0.85	34
Copper Brown	S	S	N	N	N	N	N	N/A	0.30	0.85	29
Dark Bronze	S	S	S	N	S	N	S	N/A	0.28	0.85	27
Deep Red	S	S	N	N	N	N	N	N/A	0.39	0.84	41
Evergreen	S	S	N	N	N	N	N	N/A	0.30	0.83	29
Forest Green	S	S	S	N	N	N	N	N/A	0.25	0.83	22
Hartford Green	S	S	N	N	N	N	N	N/A	0.28	0.83	26
Hemlock Green	S	S	N	N	N	N	N	N/A	0.31	0.83	30
Matte Black	S	S	N	N	N	N	N	N/A	0.26	0.89	26
Medium Bronze	S	S	S	N	S	N	S	N/A	0.31	0.85	31
Parchment	S	S	S	N	S	N	S	N/A	0.52	0.83	58
Patina Green	S	S	N	N	N	N	N	N/A	0.34	0.86	36
Royal Blue	S	S	N	N	N	N	N	N/A	0.26	0.85	25
Shasta White	S	S	S	N	S	N	S	N/A	0.60	0.84	70
Sierra Tan	S	S	S	N	S	N	S	N/A	0.39	0.85	42
Teal Green	S	S	N	N	N	N	N	N/A	0.27	0.87	27
Terra - Cotta	S	S	N	N	N	N	N	N/A	0.32	0.83	31
Zinc Grey	S	S	S	N	S	N	S	N/A	0.39	0.85	42
Acrylic-Coated Galvalume®	S	S	S	S	N/A	N/A	N/A	N/A	0.67	0.20	59
Premium Colors*											
Award Blue	S	S	N	N	N	N	N	N/A	0.17	0.83	11
Natural White	S	S	N	N	N	N	N	N/A	0.76	0.84	93
Metallic Colors*											
Antique Copper-Cote	S	S	N	N	N	N	N	N/A	0.33	0.84	34
Champagne	S	S	N	N	N	N	N	N/A	0.40	0.85	43
Copper-Cote™	S	S	N	N	N	N	N	N/A	0.51	0.85	59
Lead-Cote™	S	S	N	N	N	N	N	N/A	0.46	0.84	50
Preweathered Galvalume®	S	S	N	N	N	N	N	N/A	0.40	0.85	43
Zinc-Cote™	S	S	N	N	N	N	N	N/A	0.53	0.83	59

Testing results for Kynar 500®/Hylar 5000® coil coating applications:

- Specular Gloss: (ASTM D-523) Low and medium gloss only
- Color Uniformity: (ASTM D-2244) Color controlled both instrumentally and visually
- Dry Film Thickness: (ASTM D-7091, ASTM D-1005, NCCA 11-13, 11-14, 11-15) Primer 0.20 ± 0.05 mil, Topcoat 0.75 ± 0.05 mil
- Hardness: (ASTM D-3363, NCCA 11-12, Eagle Turquoise Pencils) HB Minimum
- Adhesion (X-Cut): (ASTM D-3359) No adhesion loss
- Adhesion (Crosshatch): (ASTM D-3359) No adhesion loss
- Abrasion Coefficient: (ASTM D-968) 100 liters/mil topcoat
- Direct Impact Flexibility: (ASTM D-2794, Gardner Impact Tester, 1/10" Distortion) Excellent, no removal
- Reverse Impact Flexibility: (NCCA Spec. 11, ASTM D-2794, Gardner Impact Tester, 5/8" ball Impact force in inch pounds equal to metal thickness) Excellent, no cracking or loss of adhesion
- Formability: (ASTM D-4145, 180° T-Bend on 1/8 Mandrel) No cracks or loss of adhesion
- Erosion: (20 years, 45° South Florida) Maximum 15% loss
- Humidity Resistance: (ASTM D-2247) Passes 2000 hours on Galvalume® and 4000 hours on Aluminum
- Acid Resistance: (ASTM D-1308, Proc. 3.1.1, 10% Sulfuric Acid spot test, 24 hour exposure) Excellent, no effect
- Salt Spray Resistance: (ASTM B-117) Passes 2000 hours on Galvalume® and 4000 hours on Aluminum
- Alkali Resistance: (ASTM D-1308, Proc. 5.2, 10% Sodium Hydroxide, 24 hour exposure) Excellent, no effect
- Detergent Resistance: (ASTM D-2248, 72 hours immersion in 3% solution at 100°F) Excellent, no effect
- Resistance to Acid Pollutants: (ASTM D 1308 Proc. 3.1.1, 24 hour exposure 10% HNO₃ vapors) Excellent, no effect
- Weathering - Color Retention: (ASTM D-2244, 20 years, 45° South Florida) Maximum 5 NBS units color change
- Weathering - Chalk Resistance: (ASTM D-4214, 20 years, 45° South Florida) Not worse than No. 8 rating

Notes:

1. ASTM - American Society for Testing Materials
2. NCCA - National Coil Coaters Association
3. Galvalume® is 55% Aluminum-Zinc alloy coated sheet steel and is a registered trademark of BIEC International Inc.

S Stock Color; Not subject to a minimum order

N Non-Stock Color; Subject to inventory on hand; 4,500 sf minimum order for 22 Gauge and 0.032 & 0.040 Aluminum

N/A Not Available

* Consult BMC on product availability for 22 Gauge and 0.032 and 0.040 Aluminum. Premium and Metallic colors are subject to a surcharge, contact BMC for additional information

**BMC SAN ANTONIO
BRANCH FACILITY**
6515 Fratt Rd.
San Antonio, TX 78218
210-650-3050
Fax: 210-650-0379

**BMC HOUSTON
BRANCH FACILITY**
1720 Maury St.
Houston, TX 77026
713-223-4971
Fax: 713-236-9422

**BMC DALLAS
BRANCH FACILITY**
2015 California Crossing
Dallas, TX 75220
972-506-8496
Fax: 972-506-8478

**BMC DENVER
BRANCH FACILITY**
7505 E. 41st Ave.
Denver, CO 80216
303-322-3703
Fax: 303-322-3810

**BMC CHICAGO
BRANCH FACILITY**
1175 Carolina Dr.
W. Chicago, IL 60185
630-231-7495
Fax: 630-231-7520

**BMC RALEIGH
BRANCH FACILITY**
1100 Corporation Pkwy #129
Raleigh, NC 27610
919-537-5705
Fax: 210-650-0379

**BMC PHOENIX
BRANCH FACILITY**
5717 W. Washington St.
Phoenix, AZ 85043
602-385-1237
Fax: 210-650-0379

**BMC ATLANTA
BRANCH FACILITY**
319 Lee Industrial Blvd.
Austell, GA 30168
770-941-5141
Fax: 770-941-7344

**BMC OKLAHOMA CITY
BRANCH FACILITY**
1400 Exchange Ave.
Oklahoma City, OK 73108
405-248-7404
Fax: 210-650-0379

**BMC KANSAS CITY
BRANCH FACILITY**
1235 Southwest Blvd.
Kansas City, KS 66103
913-227-0855
Fax: 210-650-0379

**BERRIDGE CALIFORNIA
SALES CORPORATION****
8442 Sultana Ave.
Fontana, CA 92335
562-402-2081
Fax: 562-865-7878

**BERRIDGE FLORIDA
SALES CORPORATION****
8802 Venture Cove
Tampa, FL 33637
813-335-4505
Fax: 210-650-0379

**Berridge California and Florida Sales Corporations are separate entities from Berridge Manufacturing Company



BERRIDGE MANUFACTURING COMPANY
Corporate & Sales Headquarters
2610 Harry Wurzbach San Antonio, TX 78209
210-650-3050 • Fax 210-650-0379

Manufacturing Facility
2201 Rudeloff Rd. Seguin, TX 78155
830-401-5200 • Fax: 830-303-0530

Roofs of Distinction

www.berridge.com

Spring 2018 - Berridge Color Chart - 15M Printed in the U.S.A.