



- Applicable with most roofing systems.
- Installation with continuous 20 gauge galvanized cleat.
- Pre-punched holes for proper fastener placement.
- ANSI/APRI ES-1 tested.
- International Building Code (IBC 2003 & 2006) compliant.
- Concealed splice plates (optional).
- Flange dimension fabricated to suit roofing system requirements.
- Standard finish is PVDF fluoropolymer coating in 30 standard colors.
- 35 year finish warranty.



ES-1 TESTED

| MATERIAL OPTIONS |
|-----------------------------------|
| 24 ga. (0.63 mm) galvalume steel |
| 22 ga. (0.76 mm) galvalume steel |
| 24 ga. (0.063 mm) stainless steel |
| .032" (0.8 mm) aluminum |
| .040" (1.0 mm) aluminum |
| .050" (1.2 mm) aluminum |
| .063" (1.5 mm) aluminum |

| FINISH OPTIONS |
|---|
| Standard Kynar 500 colors (see color chart for availability) |
| Custom Kynar colors |
| Plain galvanized steel or "paintgrip" |
| Mill finish aluminum |
| Anodized aluminum |
| 2B finish stainless |

International Building Code Requirement:

2003 IBC-1504.5: "Edge securement for low-slope roofs. Low slope membrane roof systems metal edge securement, except gutters, installed in accordance with Section 1507, shall be designated in accordance with ANSI/SPRI ES-1, except the basic wind speed shall be determined from Figure 1609."

