



- Spring lock installation with 20 ga. Galvanized anchor plates.
- Available in tapered or flat design.
- No exposed fasteners.
- ANSI/SPRI ES-1 tested.
- International Building Code (IBC 2003 & 2006) compliant.
- Pre-Punched holes for proper fastener placement.
- Concealed splice plates.
- Fabricated for wall widths from 6" to 24" wide.
- Standard finish is PVDF fluoropolymer coating in 30 standard and metallic colors.
- 20 year finish warranty.
- Available with factory mitered corners, transitions, and end caps.



ES-1 TESTED

International Building Code Requirement:

2003 IBC-1504.5: "Edge securement for low-slope roofs. Low slope membrane roof systems metal edge securement, except gutters, installed in accordance with Section 1507, shall be designated in accordance with ANSI/SPRI ES-1, except the basic wind speed shall be determined from Figure 1609."



MATERIAL OPTIONS
24 ga. (0.63 mm) galvalume steel
22 ga. (0.76 mm) galvalume steel
24 ga. (0.063 mm) stainless steel
.032" (0.8 mm) aluminum
.040" (1.0 mm) aluminum
.050" (1.2 mm) aluminum
.063" (1.5 mm) aluminum

FINISH OPTIONS
Standard Kynar 500 colors (see color chart for availability)
Custom Kynar colors
Plain galvanized steel or "paintgrip"
Mill finish aluminum
Anodized aluminum
2B finish stainless