


FP-150 PANEL


Flush Seam Series




OVERVIEW

The FP-150 Panel is for soffit, wall, and liner applications. It can be installed over solid substrate or on open framing (36" o.c.). Ideal applications include vertical fascias, soffit, equipment screen, and mansard walls. The FP-150 Panel is available with perforated vent strips for soffit vent application


DIAGRAMS




SMOOTH




2 PENCIL/V-RIBS



2 ROWS OF VENTING




2 ROWS OF VENTING, 2 PENCIL/V-RIBS




MATERIAL	STANDARD WIDTHS	OPTIONAL WIDTHS
24 ga. Steel	11", 15"	12", 17", 19"
22 ga. Steel	11", 15"	12", 17", 19"
.032" Aluminum	12"	
.040" Aluminum	12"	


*Aluminum & Copper available in limited quantities, please call for further availability



STRIATED



PENCIL RIBS



V RIBS

PRODUCT FEATURES

- Versatile panel for soffit, fascia, facade, and walls
- Install over solid substrate or open framing (up to 36" o.c.)
- Available smooth, striated, pencil rib, or v-rib
- Panels expand and contract freely
- Flush seam connections with hidden fasteners
- Roll-formed to exact lengths
- 35 Year finish warranty
- Net free vent area for vented panels (2 rows of perforations) up to 6.04 square inches per lineal foot
- Two rows of vents are standard