






24 Gauge | PVDF Color Offerings

** Premium Color*

				
Deep Black SR .27 SRI 25	Matte Black SR .27 SRI 25	Charcoal Gray SR .25 SRI 23	Musket Gray SR .35 SRI 35	Slate Gray SR .38 SRI 38
				
Ash Gray SR .50 SRI 56	Almond SR .61 SRI 72	Bright White SR .68 SRI 81	Bone White SR .68 SRI 81	Stone White SR .66 SRI 77
				
Cityscape SR .45 SRI 51	Extra DK Bronze SR N/A SRI N/A	Sandstone SR .60 SRI 69	Sierra Tan SR .46 SRI 50	Medium Bronze SR .31 SRI 31
				
Mansard Brown SR .26 SRI 25	Burnished Slate SR .25 SRI 33	Dark Bronze SR .28 SRI 27	Hartford Green SR .27 SRI 25	Classic Green SR .31 SRI 30
				
Hemlock Green SR .31 SRI 31	Teal SR .28 SRI 27	Slate Blue SR .33 SRI 33	Royal Blue SR .27 SRI 26	Regal Red SR .39 SRI 41
				
Colonial Red SR .33 SRI 35	Burgundy SR .27 SRI 26	Terra Cotta SR .42 SRI 45	Aged Copper * SR .27 SRI 26	Vintage * SR .30 SRI 22
				
Western Rust * SR .24 SRI 23	Copper Penny * SR .44 SRI 48	Weathered Zinc * SR .38 SRI 41	Silver * SR .56 SRI 63	Champagne * SR .47 SRI 51
				
Acrylic Coated Galvalume SR N/A SRI N/A				

35-year PVDF warranty covers performance criteria including color-fastness, fade, chalk, and film integrity.

Colors shown represent the actual colors as accurately as modern printing technology will permit.

Solar Reflectivity (SR): Solar reflectivity or reflectance is the measure of a material's ability to reflect solar energy or sunlight from its surface. SR values are numbered 0 to 1.0. A value of 0 indicates that the surface absorbs all solar energy and a value of 1.0 indicates total reflectance.

Solar Reflectance Index (SRI): The SRI is used to determine compliance with LEED requirements and is calculated according to ASTM E 1980 using values for reflectance and emissivity. To meet LEED requirements, a roofing material must have an SRI of 29 or greater for steep slope roofing and an SRI value of 78 or higher for low slope roofing.

Oil canning is an inherent part of light gauge cold-formed metal products and is not cause for coil, sheet or panel rejection.

Protective film must be removed during installation.


Coated with **Dura Coat Durapon** 70% full strength PVDF paint finishes formulated with Cool technology.

Additional standard and custom colors are available with minimum order requirements

26 Gauge | SMP Color Offerings – In stock colors




Black
SR .31 SRI 31




Matte Black
SR .26 SRI 25



Charcoal Gray
SR .37 SRI 39



Polar White
SR .64 SRI 77




Burnished Slate
SR .34 SRI 35




Evergreen
SR .35 SRI 37


26 Gauge | SMP Color Offerings – Special order *




Arctic White
SR .69 SRI 84



Alamo White
SR .64 SRI 77




Ivory
SR .64 SRI 77



Light Stone
SR .56 SRI 65




Saddle Tan
SR .47 SRI 53




Tan
SR .45 SRI 51




Taupe
SR .38 SRI 41




Buckskin
SR .33 SRI 34




Koko Brown
SR .35 SRI 37




Brown
SR .33 SRI 34



Hawaiian Blue
SR .31 SRI 31



Ocean Blue
SR .25 SRI 24




Gallery Blue
SR .26 SRI 24




Ash Gray
SR .46 SRI 52




Old Town Gray
SR .41 SRI 45




Pewter Gray
SR .35 SRI 37



Charcoal Blue Gray
SR .29 SRI 29




Rustic Red
SR .36 SRI 38




Rural Red
SR .34 SRI 35



Dark Red
SR .36 SRI 39




Crimson Red
SR .31 SRI 31




Berry
SR .29 SRI 29




Ivy Green
SR .28 SRI 27




Burgundy
SR .30 SRI 31




White CRINKLE
SR .64 SRI 77




Stone CRINKLE
SR .54 SRI 63




Gray CRINKLE
SR .43 SRI 48




Taupe CRINKLE
SR .32 SRI 34




Buckskin CRINKLE
SR .38 SRI 42




Slate CRINKLE
SR .30 SRI 31




Koko Brn CRINKLE
SR .33 SRI 34




Dark Brn CRINKLE
SR .27 SRI 27




Charcoal CRINKLE
SR .33 SRI 35




Black CRINKLE
SR .29 SRI 29




Rustic Red CRINKLE
SR .32 SRI 33



Rust CRINKLE
SR .36 SRI 39



Burgundy CRINKLE
SR .29 SRI 29




Evergreen CRINKLE
SR .33 SRI 35



Blue CRINKLE
SR .18 SRI 16



Acrylic GALVALUME®
SR N/A SRI N/A



Copper Metallic
SR .51 SRI 58

Colors shown represent the actual colors as accurately as modern printing technology will permit.

A 40-year limited paint warranty is available for all colors upon written request. Please inquire. (Outside the continental United States, please inquire). Coated with **Sherwin-Williams SMP Coil Coatings.**

Solar Reflectivity (SR): Solar reflectivity or reflectance is the measure of a material's ability to reflect solar energy or sunlight from its surface. SR values are numbered 0 to 1.0. A value of 0 indicates that the surface absorbs all solar energy and a value of 1.0 indicates total reflectance.

Solar Reflectance Index (SRI): The SRI is used to determine compliance with LEED requirements and is calculated according to ASTM E 1980 using values for reflectance and emissivity. To meet LEED requirements, a roofing material must have an SRI of 29 or greater for steep slope roofing and an SRI value of 78 or higher for low slope roofing. For more information, visit usgbc.org.

Oil canning is an inherent part of light gauge cold-formed metal products and is not cause for coil, sheet or panel rejection.

* Call for availability - minimum requirements may apply